

Product Catalogue / Die casting machines

INSPIRED BY 80 YEARS OF EXPERIENCE.
ENGINEERED BY IDRA.

 **Inspire**



THE FUTURE OF DIE CASTING IS HERE

 **IDRA**



Die casting machines

WInspire is an inspirational, technical hybrid machine, designed to combine the best available technologies for energy efficiency, precise injection control, and an optimized total cost of ownership.

- **Real-time closed-loop control** with on board data management and injection curve storage
- Water cooled **servo-motor control**
- Idra Inject Computer
- Fully enclosed guard design



HIGH PERFORMANCE AND CONSISTENT QUALITY

OL CS WInspire machines, ranging from 300 tons to 900 tons of clamping force, are designed for high performance and constant product quality.

REMOTE DIAGNOSIS AND TROUBLE SHOOTING

The system is available to achieve remote monitoring, malfunction diagnostic and trouble shooting via remote internet connection. **IDRA** can provide the customized automatic die casting cell solutions according to the products of the customer, which improves production efficiency and reduces labor cost.



Mechanical structure

The compact mechanical structure and **robust dimensions** have been designed using the same **criteria** and characteristics that have always guaranteed long life and reliability for the foundry.

Emphasis on the overall length of the machine ensures that the **required floor** space is equal to or better than the two platen product range.




SMART INJECTION

The injection unit performance is managed through **real-time closed-loop control with on board data management and injection curve storage**, powered by the **Idra Inject Computer** — enabling full remote service access and seamless **MES integration**.



RELIABILITY AND STABILITY

IDRA toggle system, ingenious design of more than 80 years experience.



ENERGY SAVING

Equipped with advanced water cooled Modrol **servo-motor control**, saves 50% or more energy consumption and reduce operation cost. The comparison is based on the same machine model equipped with a fixed displacement pump.

UNCOMPROMISING QUALITY

The **WInspire** clean and effective design, high-end specifications and compact dimensions take die-casting into a new era. Optimised in every way, **WInspire** machine is the result of Clever Italian Design and State-of-The-Art Construction Materials. Cost effective manufacturing in a competitive world.

Last generation industrial multi-touch screen monitor

Automated machine settings

Improved User Experience

Intuitive User Interface

Digital button panel

Combination touchscreen and manual controls



NOVA
NEO OPERATOR VISUAL ASSISTANT

USER FRIENDLY CONTROLS

Inject Computer 3.2

(best in class machine management software). Eliminated push button Unit using Multiple touch screens. Cell controller Single point setting for integrated peripheral automation.

Technical information




MODEL			WInspire 300	WInspire 420	WInspire 560	WInspire 700	WInspire 900
Clamping force	kN		3.000	4.360	5.850	7.500	9.200
Clamping stroke	mm		460	600	700	780	900
Die height	min.	mm	250	250	300	400	450
	max.	mm	650	700	800	900	1000
Platen dimensions (H x V)	mm		860x860	1.019x1.019	1.160x1.160	1.320x1.320	1.400x1.400
Space between tie bars	mm		560x560	669x669	760x760	860x860	910x910
Ejection force	kN		157	246	246	385	385
Ejection stroke	mm		105	140	165	175	200
Injection force (back pressure 0 bar)	kN		419	457	531	615	806
Injection stroke	mm		450	500	600	650	700
Plunger diameter	mm		50-70	60-80	70-90	80-100	80-110
Shot weight (Al alloy)	kg		1,6 - 3,2	2,6 - 4,7	4,3 - 7,1	6,1 - 9,5	6,5 - 12,4
Casting pressure (intens, back pressure 0 bar)	bar		2.100-1.050	1.600-900	1.350-800	1.200-750	160-80
Casting area	cm ²		140-285	270-480	430-730	625-1.000	575-1.150
Max. casting area (400 bar)	cm ²		750	1.090	1.463	1.875	2.300
Shot injection position	mm		0, -125	0, -200	0, -270	0, -300	0, -350
Working pressure	bar		160	160	160	160	160

The technical information and pictures shown are subject to change and may be modified and/or improved as considered necessary.

WInspire - The Future of Die Casting

*"Innovation doesn't happen by chance.
It is engineered."*



EN

www.idragroup.com

IDRA S.r.l.

Via dei Metalli, 2
25039 Travagliato (BS)
Italy
Tel. +39 030 2011 1
Fax +39 030 2002 345
sales.italy@idragroup.com

IDRAPRESSE MEXICO S. de R.L. de C.V.

Carretera Saltillo 308 Int. 7,
Provienda del Poniente Sector Uno
66129, Santa Catarina
Nuevo León, Mexico
Tel. +52 1 81 3581 4504
sales.mexico@idragroup.com

IDRA PRESSEN GmbH

Eisenbahnstrasse 6
73630 Remshalden Grunbach
Deutschland
Sales: +49 163 6364 802
Service: +49 163 6364 801
sales.germany@idragroup.com

IDRA CHINA LTD.

No. 42 MinYi Road
SongJiang Area
201612 Shanghai
P.R. China
Tel. +86 21 68751216
sales.china@idragroup.com
www.idrachina.com

IDRA NORTH AMERICA INC.

1510 North Ann St.
Kokomo, Indiana 46901
USA
Tel. +1 765 459 0085
Fax +1 765 457 0095
sales.usa@idragroup.com



www.idragroup.com



Management
System
ISO 9001:2015
ISO 14001:2015
ISO 45001:2018
www.tuv.com
ID 9000004771



The technical information
and pictures shown are subject to change
and may be modified and/or improved
as considered necessary.



WInspire_EN_15062026_06_26